



ATTESTATION of conformity with European Directives

BV LCIE CHINA Number 1966AS02SXP30720-N2
Product PV inverter (Grid-tied photovoltaic inverter)
Reference X1-6.0-T-D, X1-6.0-T-N, X1-7.0-T-D, X1-7.0-T-N, X1-8.0-T-D, X1-8.0-T-N
Issued to SolaX Power Network Technology (Zhe jiang) Co., Ltd.
Address No. 288 Shizhu Road, Tonglu Economic Development Zone, Dongxing District 311500,
Tonglu City, Zhejiang Province, People's Republic of China
Manufacturer SolaX Power Network Technology (Zhe jiang) Co., Ltd.
Technical characteristics See below table

The submitted sample of the above equipment has been tested for **CE** marking according to following European Directive and following standards:

LVD Directive 2014/35/EU *

* Thanks to note that from April 20th 2016; this directive will be replaced by the new LVD directive, 2014/35/EU.

Standards	Report number	Report date
EN 62109-1:2010	SXP-19JA0343FTSHP-1-R2	2022-12-24
EN 62109-2:2011	SXP-19JA0343FTSHP-2-R2	

The referred test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the essential requirements in the specified European Directive

This verification does not imply assessment of the production of the product

The **CE** marking may be affixed if all relevant and effective European Directives with **CE** are applicable

Shanghai (P.R. China), March 16th, 2023



This document shall not be reproduced, except in full, without the written approval of BV LCIE China. Information given in this document, are related to the tested specimen of the described electrical sample.



**BUREAU
VERITAS**

Model / Type :	X1-6.0-T-D X1-6.0-T-N	X1-7.0-T-D X1-7.0-T-N	X1-8.0-T-D X1-8.0-T-N
MPP DC voltage range [V] :	100-530		
Max. Input DC voltage [V] :	550		
Max. Input DC current [A] :	14/28		
Output AC voltage [V] :	220/230/240 ~, 50/60Hz		
Max. Output AC current [A] :	28,7	33,5	38,3
Output power [VA]:	6000(Rated), 6600(Max.)	7000(Rated), 7700(Max.)	7000(Rated), 8800(Max.)

Page 2 of 2